



5G PROBE – Model 01G

Electric Field Measurement in the n78 Band

TECHNICAL SPECIFICATIONS	
Sensor Type	Tri-axial isotropic
Frequency Range	3.3 ÷ 3.8 GHz
Frequency Response	± 2 dB
Anisotropy	±0.7 dB @3.5GHz
Linearity	± 0.5 dB (1 ÷ 100 V/m)
Measurement range (rms)	0,5 ÷ 150 V/m
Dynamic Range	50 dB
Temperature error	0.01 dB/°C
Magnetic field rejection	>20 dB

GENERAL CHARACTERISTICS	
Recommended calibration interval	24 months
Operating Temperature	0°C ÷ 50°C
Humidity	Up to 90% non-condensing
Dimensions	250 x 40 Ø(mm)
Weight	130g
Country of origin	Italy
Certification	ISO 9001:2015 calibration according to IEEE 1309:2013 standard

PRELIMINARY. Specifications subject to change without notice.



Piazza delle Azalee, 13/14 05018 – Orvieto (TR) - Italy
Tel. +39 0763 393291 info@microrad.it - www.microrad.it



5G PROBE – Model 01G

Electric Field Measurement in the n78 Band



PRELIMINARY. Specifications subject to change without notice.



Piazza delle Azalee, 13/14 05018 – Orvieto (TR) - Italy
Tel. +39 0763 393291 info@microrad.it - www.microrad.it



5G PROBE – Model 01G

Electric Field Measurement in the n78 Band

Key Features:

- Frequency Range: 3.3 GHz ÷ 3.8 GHz
- Dynamic range: 50 dB
- Anisotropy: $\pm 0.7\text{dB}@3.5\text{GHz}$
- Sensitivity: 0.5 V/m
- Measurement Range: 150 V/m

Compatibility:

- NHT3DL and NHT310F meters
- MicroLink software for PCs running Windows

Applications:

- 5G telecommunication systems operating in the n78 band

PRELIMINARY. Specifications subject to change without notice.



Piazza delle Azalee, 13/14 05018 – Orvieto (TR) - Italy
Tel. +39 0763 393291 info@microrad.it - www.microrad.it




5G PROBE – Model 01G

Electric Field Measurement in the n78 Band

Description:

Isotropic probe specifically designed for measuring 5G signals in the n78 band.

The probe is equipped with a band-pass filter on each axis, enabling the rejection of out-of-band interference.



PRELIMINARY. Specifications subject to change without notice.



Piazza delle Azalee, 13/14 05018 – Orvieto (TR) - Italy
Tel. +39 0763 393291 info@microrad.it - www.microrad.it